

**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**
**1.1. Product identifier**

BriteGuard Pro

**Further trade names**

BO 5850101, 100 ml

BO 5850500, 500 ml

BO 5855000, 5 l

BO 6850500, 500 ml

BO 6855000, 5 l

UFI: SGAR-PF35-X3HH-AHAG

**1.2. Relevant identified uses of the substance or mixture and uses advised against**
**Use of the substance/mixture**

Solvent-borne coatings

**1.3. Details of the supplier of the safety data sheet**

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

**1.4. Emergency telephone number:** Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification**
**2.1. Classification of the substance or mixture**
**GB CLP Regulation**

Flam. Liq. 2; H225

Eye Irrit. 2; H319

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**
**GB CLP Regulation**
**Hazard components for labelling**

propan-2-ol; isopropyl alcohol; isopropanol

**Signal word:** Danger

**Pictograms:**

**Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 2 of 9

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

**Additional advice on labelling**

The product is classified and labelled in accordance with EC directives or respective national laws.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (GB CLP Regulation)	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	>95 %
	200-661-7	
	603-117-00-0	
	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
1174522-15-6	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	<5 %
	927-285-2	
	01-2119480162-45	
	Asp. Tox. 1; H304 EUH066	

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	>95 %
		inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg	
1174522-15-6	927-285-2	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	<5 %
		inhalation: LC50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

Take off immediately all contaminated clothing.

**After inhalation**

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

**After contact with skin**

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists, consult a specialist.

**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 3 of 9

**After ingestion**

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

high volume water jet

**5.2. Special hazards arising from the substance or mixture**

In use may form flammable/explosive vapour-air mixture.

Fire may cause evolution of: Carbon monoxide, Carbon dioxide )

**5.3. Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

**Additional information**

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation.

Keep away from heat and sources of ignition.

Avoid contact with skin and eyes. Do not breathe vapour.

**6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Local authorities should be advised if significant spillages cannot be contained.

**6.3. Methods and material for containment and cleaning up****Other information**

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations.

Provide room air exhaust at ground level.

Avoid formation of aerosol. Do not breathe vapour/aerosol.

**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 4 of 9

Avoid contact with the skin and the eyes.

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.

**Advice on general occupational hygiene**

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

**7.2. Conditions for safe storage, including any incompatibilities**
**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

**8.2. Exposure controls**
**Appropriate engineering controls**

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

## Safety Data Sheet

according to UK REACH Regulation

### BriteGuard Pro

Revision date: 17.08.2023

Product code: BO5850500

Page 5 of 9

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

safety glasses with side-shields conforming to EN166

##### Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber)  $\geq 0,5\text{mm}$ , NBR (Nitrile rubber)  $\geq 0,35\text{mm}$

Breakthrough time:  $\geq 480$  min.

##### Skin protection

impervious clothing

##### Respiratory protection

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	clear
Odour:	alcoholic

#### Test method

Melting point/freezing point:	-89,5 °C
Boiling point or initial boiling point and boiling range:	82 °C
Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Flash point:	12 °C
Auto-ignition temperature:	425 °C
pH-Value (at 20 °C):	7
Water solubility: (at 20 °C)	soluble OECD 116
Vapour pressure: (at 20 °C)	48 hPa
Density (at 20 °C):	0,79 g/cm <sup>3</sup>

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

In use, may form flammable/explosive vapour-air mixture.

##### Self-ignition temperature

not auto-flammable

#### Other safety characteristics

Solvent content:	99 %
Viscosity / dynamic: (at 20 °C)	2,43 mPa·s

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal processing.

### 10.2. Chemical stability

No decomposition if used as directed.

### 10.3. Possibility of hazardous reactions

**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 6 of 9

Vapours may form explosive mixture with air.

**10.4. Conditions to avoid**

Keep away from heat and sources of ignition.  
Take action to prevent static discharges.

**10.5. Incompatible materials**

strong acids and oxidizing agents

**10.6. Hazardous decomposition products**

None known.

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in GB CLP Regulation**
**Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	4570	Rat	
	dermal	LD50 mg/kg	13400	Rabbit	
	inhalation (4 h) vapour	LC50	30 mg/l	Rat	
1174522-15-6	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 mg/kg	>5000	Rat	
	dermal	LD50 mg/kg	>5000	Rabbit	
	inhalation (4 h) vapour	LC50 mg/l	>5000	Rat	

**11.2. Information on other hazards**
**Other information**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**SECTION 12: Ecological information**
**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 mg/l	72 h	Desmodesmus subspicatus		

**12.2. Persistence and degradability**

Readily biodegradable, according to appropriate OECD test.

**12.3. Bioaccumulative potential**

**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 7 of 9

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16

**12.4. Mobility in soil**

The product evaporates readily..

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Further information**

Water hazard class 1: slightly water endangering

Do not let product enter drains.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

In accordance with local and national regulations.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - used product**

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

**List of Wastes Code - contaminated packaging**

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

**SECTION 14: Transport information**
**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1219
<b>14.2. UN proper shipping name:</b>	ISOPROPANOL (ISOPROPYL ALCOHOL)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33

**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 8 of 9

Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Special Provisions: 601  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** Isopropanol  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: A180  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

none

**14.7. Maritime transport in bulk according to IMO instruments**

not relevant



**Safety Data Sheet**

according to UK REACH Regulation

**BriteGuard Pro**

Revision date: 17.08.2023

Product code: BO5850500

Page 9 of 9

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 99 % (781 g/l)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information**
**Changes**

This data sheet contains changes from the previous version in section(s): 2,9.

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*