

**Safety Data Sheet**

according to UK REACH Regulation

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

UV Adhesive VERIFIX MV 760 VIS

**Further trade names**

BO MV76V10, 100 g

BO MV76V25, 250 g / BO MV76V25S, Spacer, 250 g

BO MV76V1K, 1000 g

UFI: FY7M-1SJ9-5361-38FV

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

adhesives

**1.3. Details of the supplier of the safety data sheet**

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

**1.4. Emergency telephone number:** Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Skin Corr. 1A; H314  
Eye Dam. 1; H318  
Skin Sens. 1; H317  
STOT SE 3; H335  
Aquatic Acute 1; H400  
Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate  
acrylic acid, prop-2-enoic acid  
2-hydroxyethyl methacrylate  
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

**Signal word:** Danger**Pictograms:**

**Safety Data Sheet**

according to UK REACH Regulation

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 2 of 10

**Hazard statements**

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Precautionary statements**

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Chemical characterization**

Methacrylate/Acrylate resin(s).

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
73324-00-2	Urethane acrylate			< 50%
	615-966-4		-	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
79-10-7	acrylic acid, prop-2-enoic acid			< 25 %
	201-177-9	607-061-00-8	01-2119452449-31	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Aquatic Acute 1; H226 H332 H312 H302 H314 H400			
868-77-9	2-hydroxyethyl methacrylate			< 10%
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			< 2%
	278-355-8	015-203-00-X	01-2119972295-29	
	Repr. 2, Skin Sens. 1B, Aquatic Acute 2, Aquatic Chronic 2; H361f H317 H401 H411			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to UK REACH Regulation

### UV Adhesive VERIFIX MV 760 VIS

Revision date: 20.10.2023

Product code: BOMV76V10

Page 3 of 10

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
79-10-7	201-177-9	acrylic acid, prop-2-enoic acid	< 25 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 1100 mg/kg; oral: LD50 = 500 mg/kg STOT SE 3; H335: >= 1 - 100 Aquatic Acute 1; H400: M=1	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	< 10% %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = 5050 mg/kg	
75980-60-8	278-355-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	< 2% %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

First aider: Pay attention to self-protection!  
Get medical advice/attention if you feel unwell.

###### After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

###### After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

###### After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

###### After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract  
Skin contact : May cause an allergic skin reaction.  
Eye contact : Causes serious eye damage.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO<sub>2</sub>)

###### Unsuitable extinguishing media

Full water jet

##### 5.2. Special hazards arising from the substance or mixture

Burning produces irritant fumes. Carbon monoxide, Carbon dioxide, Hydrocarbons, Nitrogen oxides (NO<sub>x</sub>)

##### 5.3. Advice for firefighters

Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
In the event of fire, wear self-contained breathing apparatus.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

## Safety Data Sheet

according to UK REACH Regulation

### UV Adhesive VERIFIX MV 760 VIS

Revision date: 20.10.2023

Product code: BOMV76V10

Page 4 of 10

#### General advice

Wear personal protection equipment (refer to section 8).  
Provide adequate ventilation.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3. Methods and material for containment and cleaning up

##### Other information

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

#### 6.4. Reference to other sections

Personal protection equipment: see section 8  
Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid contact with skin and eyes.  
Do not eat, drink or smoke when using this product.  
Ensure adequate ventilation.

#### Advice on protection against fire and explosion

No special technical protective measures required.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke.  
Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

#### Further information on handling

Avoid: UV-radiation/sunlight

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.  
Keep container tightly closed. Keep locked up.  
Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

### 7.3. Specific end use(s)

adhesive

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
79-10-7	Acrylic acid	10	29		TWA (8 h)	WEL
		20	59		STEL (1 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 5 of 10

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
79-10-7	acrylic acid, prop-2-enoic acid		
Worker DNEL, long-term	inhalation	systemic	30 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	30 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	30 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	30 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
79-10-7	acrylic acid, prop-2-enoic acid	
Freshwater	0,003 mg/l	
Freshwater (intermittent releases)	0,0013 mg/l	
Marine water	0,0003 mg/l	
Freshwater sediment	0,0236 mg/kg	
Marine sediment	0,00234 mg/kg	

**8.2. Exposure controls**
**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

safety glasses with side-shields conforming to EN166

**Hand protection**

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Recommended material: NBR (Nitrile rubber), VITON

Unsuitable material: Natural fibres (e.g. cotton)

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

Usually no personal respiratory protection necessary. When using do not eat, drink or smoke.

In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)

Respirator with filter for organic vapour. Recommended Filter type: A (P2)

**SECTION 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic

**9.2. Other information**
**Other safety characteristics**

Solvent content:	0%
Viscosity / dynamic: (at 23 °C)	1500 mPa·s

**Further Information**

not auto-flammable

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 6 of 10

**SECTION 10: Stability and reactivity**
**10.1. Reactivity**

Light / UV-radiation/sunlight

Oxidising agent, strong

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep cool. Protect from sunlight. Heat, flames and sparks.

In case of light influence: Polymerisation

**10.5. Incompatible materials**

Reducing agent, strong. Oxidising agent, strong

strong acids and strong bases

**10.6. Hazardous decomposition products**

No decomposition if stored and applied as directed.

Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),

 Carbon dioxide (CO<sub>2</sub>), Hydrocarbons

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in GB CLP Regulation**
**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
79-10-7	acrylic acid, prop-2-enoic acid				
	oral	LD50 mg/kg 500	Rat		
	dermal	LD50 mg/kg 1100	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 mg/kg 5050	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 mg/kg >5000	Rat	OECD 401	
	dermal	LD50 mg/kg >2000	Rat	OECD 402	

**Irritation and corrosivity**

Causes severe skin burns and eye damage.

Causes serious eye damage.

**Safety Data Sheet**

according to UK REACH Regulation

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 7 of 10

**Sensitising effects**

May cause an allergic skin reaction. (2-hydroxyethyl methacrylate; Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; acrylic acid, prop-2-enoic acid)

Inhalative specific target organ toxicity (single exposure)

@05888.33.5DE: Category 3

acrylic acid; prop-2-enoic acid: Category 3

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**
**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50 227 mg/l	96 h	Pimephales promelas		
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute fish toxicity	LC50 10 mg/l	96 h	Danio rerio (zebrafish)		
	Acute crustacea toxicity	EC50 3,53 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202	
	Acute bacteria toxicity	(EC50 2,01 mg/l)		Pseudokirchneriella subcapitata	OECD 201	

**12.2. Persistence and degradability**

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	aerob	0-10%	28		
	Not readily biodegradable (according to OECD criteria)				

**12.3. Bioaccumulative potential**
**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
79-10-7	acrylic acid, prop-2-enoic acid	0,35
868-77-9	2-hydroxyethyl methacrylate	0,47

**BCF**

CAS No	Chemical name	BCF	Species	Source
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	18-22		

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**Safety Data Sheet**

according to UK REACH Regulation

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 8 of 10

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Further information**

No data is available on the product itself.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Consult the appropriate local waste disposal expert about waste disposal.

**List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**
**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1760
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, N.O.S. (acrylic acid; prop-2-enoic acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8



Classification code:	C9
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1760
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, N.O.S. (acrylic acid; prop-2-enoic acid)



**Safety Data Sheet**

according to UK REACH Regulation

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 9 of 10

**14.3. Transport hazard class(es):**

8

**14.4. Packing group:**

III

Hazard label:

8



Classification code:

C9

Special Provisions:

274

Limited quantity:

5 L

Excepted quantity:

E1

**Marine transport (IMDG)**
**14.1. UN number or ID number:**

UN 1760

**14.2. UN proper shipping name:**

CORROSIVE LIQUID, N.O.S.. (Acrylic Acid)

Marine pollutant (@05888.33.5DE, Acrylic Acid)

**14.3. Transport hazard class(es):**

8

**14.4. Packing group:**

III

Hazard label:

8



Special Provisions:

223, 274

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**
**14.1. UN number or ID number:**

UN 1760

**14.2. UN proper shipping name:**

CORROSIVE LIQUID, N.O.S. (Acrylic Acid)

**14.3. Transport hazard class(es):**

8

**14.4. Packing group:**

III

Hazard label:

8



Special Provisions:

A3 A803

Limited quantity Passenger:

1 L

Passenger LQ:

Y841

Excepted quantity:

E1

IATA-packing instructions - Passenger:

852

IATA-max. quantity - Passenger:

5 L

IATA-packing instructions - Cargo:

856

IATA-max. quantity - Cargo:

60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

Yes


**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Safety Data Sheet**

according to UK REACH Regulation

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 20.10.2023

Product code: BOMV76V10

Page 10 of 10

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

 2004/42/EC (VOC): 0 %  
0 g/l

Information according to 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**
**Changes**

This data sheet contains changes from the previous version in section(s): 2.

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

**Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*