

Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 1 of 8

1. Identification
Product identifier

UV Adhesive VERIFIX LV 740

Further trade names

BO LV74002, 20 g
 BO LV74010, 100 g
 BO LV74025, 250 g
 BO LV7401K, 1000 g

Recommended use of the chemical and restrictions on use
Use of the substance/mixture

adhesives

Details of the supplier of the safety data sheet
Manufacturer

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

Trader of the product

Company name:	Bohle America, Inc.
Street:	10924 Granite Street, Suite 200
Place:	USA-NC 28273 Charlotte
e-mail (Contact person):	sales@bohle.com

Emergency phone number: Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

2. Hazard(s) identification
Classification of the chemical
29 CFR Part 1910.1200

Skin corrosion/irritation: Skin Corr. 1A
 Serious eye damage/eye irritation: Eye Dam. 1
 Respiratory or skin sensitization: Skin Sens. 1
 Specific target organ toxicity single exposure: STOT SE 3 (respiratory tract irritation)

Label elements
29 CFR Part 1910.1200

Signal word: Danger

Pictograms:


Hazard statements

Causes severe skin burns and eye damage
 May cause an allergic skin reaction
 May cause respiratory irritation

Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 2 of 8

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Rinse mouth. Do NOT induce vomiting.
 If on skin: Wash with plenty of Water and soap.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Immediately call a poison center/doctor.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.

3. Composition/information on ingredients

Mixtures

Chemical characterization

Methacrylate/Acrylate resin(s).

Hazardous components

CAS No	Components	Quantity
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	47.5 %
73324-00-2	Urethane acrylate	20 %
79-10-7	acrylic acid, prop-2-enoic acid	17.5 %
868-77-9	2-hydroxyethyl methacrylate	15 %

4. First-aid measures

Description of first aid measures

General information

First aider: Pay attention to self-protection!
 Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract
 Skin contact : May cause an allergic skin reaction.
 Eye contact : Causes serious eye damage.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 3 of 8

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO₂)**Unsuitable extinguishing media**

Full water jet

Specific hazards arising from the chemicalBurning produces irritant fumes. Carbon monoxide, Carbon dioxide, Hydrocarbons, Nitrogen oxides (NO_x)**Special protective equipment and precautions for fire-fighters**

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up**Other information**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

Reference to other sections

Personal protection equipment (PPE): see section 8

Disposal: see section 13

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Ensure adequate ventilation.

Advice on protection against fire and explosion

No special technical protective measures required.

Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke.

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Further information on handling

Avoid: UV-radiation/sunlight

Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 4 of 8

Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

8. Exposure controls/personal protection
Control parameters
Exposure limits

CAS No	Substance	ppm	mg/m ³	f/cc	Category	Origin
79-10-7	Acrylic acid	2	6		TWA (8 h)	REL

Exposure controls
Individual protection measures, such as personal protective equipment
Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Recommended material: NBR (Nitrile rubber), VITON

Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respiratory protection necessary. When using do not eat, drink or smoke.

In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)

Respirator with filter for organic vapour. Recommended Filter type: A (P2)

9. Physical and chemical properties
Information on basic physical and chemical properties

Physical state:	Liquid
Color:	colorless
Odor:	characteristic

Flash point:	80 °C	Test method
pH-Value (at 21 °C):	2,5	DIN 51755 5% emulsion

Other information
Other safety characteristics

Solvent content:	0%
Viscosity / dynamic: (at 23 °C)	80 mPa·s

10. Stability and reactivity
Reactivity

Light / UV-radiation/sunlight

Oxidizing agent, strong

Chemical stability

Stability: Stable

Stable under recommended storage conditions.

Possibility of hazardous reactions

Hazardous reactions: May occur

Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 5 of 8

No known hazardous reactions.

Conditions to avoid

Keep cool. Protect from sunlight. Heat, flames and sparks.
In case of light influence: Polymerisation

Incompatible materials

Reducing agent, strong. Oxidizing agent, strong
strong acids and strong bases

Hazardous decomposition products

No decomposition if stored and applied as directed.
Thermal decomposition can lead to the escape of irritating gases and vapors. Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrocarbons

11. Toxicological information
Information on toxicological effects
Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
	oral	LD50 mg/kg >5000	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		
79-10-7	acrylic acid, prop-2-enoic acid				
	oral	LD50 mg/kg 500	Rat		
	dermal	LD50 mg/kg 1100	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 mg/kg 5050	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		

Irritation and corrosivity

Causes severe skin burns and eye damage
Causes serious eye damage

Sensitizing effects

May cause an allergic skin reaction (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; 2-hydroxyethyl methacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause respiratory irritation (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)
Inhalative specific target organ toxicity (single exposure)

@05888.33.5DE: Category 3

acrylic acid; prop-2-enoic acid: Category 3

Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 6 of 8

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.
 Carcinogenicity (IARC): Acrylic acid (CAS 79-10-7) is listed in group 3.
 Carcinogenicity (NTP): No ingredient of this mixture is listed.

Aspiration hazard

Based on available data, the classification criteria are not met.

12. Ecological information
Ecotoxicity

CAS No	Components					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate					
	Acute fish toxicity	LC50 mg/l	0,704	96 h	Danio rerio (zebrafish)	OECD 203
	Crustacea toxicity	NOEC mg/l	0,092	21 d	Daphnia magna (Big water flea)	
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	

Partition coefficient n-octanol/water

CAS No	Components	Log Pow
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	4,52
79-10-7	acrylic acid, prop-2-enoic acid	0,35
868-77-9	2-hydroxyethyl methacrylate	0,47

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

No data is available on the product itself.

13. Disposal considerations
Waste treatment methods
Disposal recommendations

Consult the appropriate local waste disposal expert about waste disposal.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information
U.S. DOT 49 CFR 172.101
UN number or ID number:

UN 1760

Proper shipping name:

corrosive liquids, n.o.s. (Acrylic Acid)

Transport hazard class(es):

8

Packing group:

II

Hazard label:

8



Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 7 of 8

Marine transport (IMDG)
UN number or ID number:

UN 1760

UN proper shipping name:

 CORROSIVE LIQUID, N.O.S. (Acrylic Acid)
 Marine pollutant (@05888.33.5DE, Acrylic Acid)

Transport hazard class(es):

8

Packing group:

II

Hazard label:

8



Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

EmS:

F-A, S-B

Air transport (ICAO-TI/IATA-DGR)
UN number or ID number:

UN 1760

UN proper shipping name:

CORROSIVE LIQUID, N.O.S. (Acrylic Acid)

Transport hazard class(es):

8

Packing group:

II

Hazard label:

8



Special Provisions:

A3 A803

Limited quantity Passenger:

0.5 L

Passenger LQ:

Y840

Excepted quantity:

E2

IATA-packing instructions - Passenger:

851

IATA-max. quantity - Passenger:

1 L

IATA-packing instructions - Cargo:

855

IATA-max. quantity - Cargo:

30 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes


15. Regulatory information
U.S. Regulations
National regulatory information

SARA Section 304 CERCLA:

Acrylic acid (79-10-7): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate (5888-33-5): Immediate (acute) health hazard

Urethane acrylate (73324-00-2): Immediate (acute) health hazard

Acrylic acid (79-10-7): Fire hazard, Immediate (acute) health hazard

2-hydroxyethyl methacrylate (868-77-9): Immediate (acute) health hazard

SARA Section 313 Toxic release inventory:

Acrylic acid (79-10-7): De minimis limit = 1.0 %, Reportable threshold = Standard

Clean Air Act Section 112(b):

Safety Data Sheet

according to 29 CFR 1910.1200(g)

UV Adhesive VERIFIX LV 740

Revision date: 10/20/2023

Product code: BOLV74010

Page 8 of 8

Acrylic acid (79-10-7)

State Regulations
Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information
Hazardous Materials Information Label (HMIS)

Health:	3
Flammability:	1
Physical Hazard:	0

NFPA Hazard Ratings

Health:	2
Flammability:	1
Reactivity:	0
Unique Hazard:	


Changes

Revision date:	10/20/2023
Revision No:	2,10

This data sheet contains changes from the previous version in section(s): 2.

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)